



NATSON

Edelstahl- und Holzmanufaktur

Maße:



CONSULTING
CONSTRUCTION
COMPLETION

Waiter Station Counter. WS-Counter_0368.

- ▶ The Waiter Station is designed as a built-in unit and complies fully with the requirements of USPH.
- ▶ Material: stainless steel 1.4301, brushed (240 grain)
- ▶ Thickness: Body 1,5 mm, front skin 1,25 mm.
- ▶ The counter is fitted with a U-shaped trim front cover bevelled to a 10 mm radius to allow easier cleaning of the interior corners. To save weight the cover is manufactured without side panelling. If required decorative wooden boards can be fastened to the side walls and to the base.
- ▶ The drawer is integrated in a 3 mm thick stainless steel guide rail system and can carry loads of up to 100 kilograms. For extra stability the rails are fastened to the counter's inner walls which are especially reinforced.
- ▶ The drawer is fitted with a retaining device in the rear area, which prevents accidental opening. Whilst magnets are installed in the front area to prevent the drawer from springing back when opened.
- ▶ A removable container in the drawer is made from 1,5 mm stainless steel, brushed both sides (width 256 mm, depth 530 mm, height 100 mm, corner radius 10 mm).
- ▶ The sanitary area in the lower part of the counter is fitted with a swivelling door and contains a removable shelf, supported by four CNS bolts.
- ▶ All of the doors (width 308,5 mm, height 490 mm, thickness 17 mm) are independently replaceable and can be easily removed for cleaning. The doors are fitted with magnetic closers and shock absorbers in addition to 60 mm long hinges welded to the counter unit.
- ▶ When the counter is installed the gap between the counter and the adjacent unit amounts to **less than 1 mm**.



**You are interested or have questions about the product?
Then please get in touch with us; we are only too pleased
to help.**

**Telefon: +49-(0)3631-918220
Telefax: +49-(0)3631-918221
E-Mail: info@natson.de**